

Email: sales@laboratoryinstrumentindia.com

**Product Name :**Digital Strain Display

Product Code: LBNY-0005-1380004



## **Description:**

The Digital Strain Display accepts up to 16 channels from strain gauges connected in quarter, half or full bridge. The display is fully programmable to match the strain gauges and their bridgeconnections. The display includes precision internal make-up resistors towork with half bridge connections if needed. For quarter bridge connection youneed suitable external make-up resistors or dummy gauges. For use with most types of metal-foil strain gauges, the Digital Strain Display connects to most types of strain bridge connections togive direct readings of strain. Two channels includeadditional individually adjusted dynamic outputs. They can connect to suitable instruments, such as an oscilloscope or a chart recorder for measurement oftransient strains. Also supplied is a tool that crimps the connectors to the cable. The connectors areself-locking, reliable, and secure and need no soldering. Supplied with the Digital Strain Display is a reel of cableand connectors to fit the input sockets of the Digital Strain Display.

## Channels:

Channels 15 and 16 may also be used for dynamic strain output. Sixteen all channels may be used for slow-changing or staticstrain measurement.

## **Technical Specification:**

Packed volume: 0.04 m3

Dimensions: 130 mm x 310 mm x 380 mm

Nett weight: 4.5 kg Gross weight: 9 kg.



## **Laboratory Instrument India**