



Email : sales@laboratoryinstrumentindia.com

**Product Name :**  
SLOGGING WRENCH RING SPANNERS

**Product Code :**  
LBNY-0029-2200028



**Description :**

Forged from HIGH GRADE Selected Alloy Steel Heavy Duty Bi-hexagonal spanner with short, strong profiled handle with durable striking end and its 12 point opening allows it to be manipulated even in confined space.  
FINISH: Black & Chrome Finish

**Technical Specification :**

| SIZE(MM) | NET WT.IN GMS. | LENGTH(MM) | NET WT. / CTN.(KGS) | GR. WT.(KGS) |
|----------|----------------|------------|---------------------|--------------|
| 27 260   | 167            | 20.8       | 22.3                |              |
| 27 288   | 179            | 23.04      | 24.54               |              |
| 30 392   | 191            | 23.52      | 25.02               |              |
| 32 403   | 197            | 24.18      | 25.68               |              |
| 33 403   | 197            | 24.18      | 25.68               |              |
| 34 466   | 196            | 23.3       | 24.8                |              |
| 36 596   | 206            | 21.456     | 22.956              |              |
| 38 647   | 224            | 19.41      | 20.91               |              |
| 41 760   | 231            | 22.8       | 24.3                |              |
| 42 760   | 231            | 22.8       | 24.3                |              |
| 46 947   | 241            | 22.728     | 24.228              |              |
| 50 1202  | 255            | 24.04      | 25.54               |              |
| 5 1396   | 271            | 22.336     | 23.836              |              |
| 60 1492  | 279            | 23.872     | 25.372              |              |
| 65 1810  | 29             | 21.72      | 23.22               |              |
| 70 2931  | 323            | 23.448     | 24.948              |              |

---

|     |       |     |       |       |
|-----|-------|-----|-------|-------|
| 75  | 3040  | 330 | 24.32 | 25.82 |
| 80  | 4700  | 361 | 28.2  | 29.7  |
| 85  | 4550  | 361 | 18.2  | 19.7  |
| 90  | 5150  | 390 | 20.6  | 22.1  |
| 95  | 4900  | 390 | 19.6  | 21.1  |
| 100 | 6000  | 400 | 24    | 25.5  |
| 105 | 5850  | 400 | 23.4  | 24.9  |
| 110 | 8000  | 450 | 16    | 17.5  |
| 115 | 7850  | 450 | 15.7  | 17.2  |
| 120 | 11600 | 495 | 11.6  | 13.1  |
| 125 | 11400 | 495 | 11.4  | 12.9  |
| 130 | 13500 | 520 | 13.5  | 15    |
| 135 | 13300 | 520 | 13.3  | 14.8  |
| 140 | 13100 | 520 | 13.1  | 14.6  |
| 145 | 18200 | 580 | 18.2  | 19.7  |
| 150 | 18000 | 580 | 18    | 19.5  |
| 155 | 17800 | 580 | 17.8  | 19.3  |



**Laboratory Instrument India**